

LED CEILING LIGHT





























	65 C F>21lm/W
odel	KONS KIC934/A
GHT SOURCE	LED
ORKING VOLTAGE	AC90V-AC260V
OWER	8W/12W/20W/40W
EAM ANGLE	15°/24°/36°
OLOR TEMPERATURE	3000K-6000K
GHT EFFICIENCY	>80lm/W
LOR RENDERING INDEX	Ra>85
PERATING TEMPERATURE	-25-+40
ATED LIFE HOURS	35,000-50000H
D CHIP	CREE, SAMSUNG, EPISTAR

DESCRIPTIONS

- High efficiency, low energy consumption.
- Good quality beam.
- Long life span 50000 hours.
- Flexible control, Dimming by changing current
- Ecological, The waste can be recycled.
- No pollution and mercury.

Note

- ⚠ This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.
- Do not attempt to install or use a fixture until you read and understand the installation instructions and safety labels.
- Fixtures have line voltage risk of shock and no user serviceable parts. Do not attempt to open them.
- Do not hot swap fixtures. Ensure that power to the series is off before connecting or disconnecting individual fixtures.
- Do not use a fixture if the lens, housing, or power cables are damaged.
- Do not use a fixture for any voltage for which it is not rated. Do not exceed the specified voltage and current input for any fixture.
- Caution led radiation do not stare into beam class 2 LED products.